

# DCP800APPR

## SPECIALTY POLYESTER DOUBLE-COATED TAPE

### DESCRIPTION

Polyester (PET) film coated on both sides with a solvent based acrylic adhesive. Delivers high initial tack and high peel adhesion and secure bonding in high temperatures. Excellent resistance to plasticizers, solvents, chemicals, aging and heat. Features a MOPP film liner.

### PRODUCT APPLICATION

For permanent bonding of similar or dissimilar surfaces such as ABS, polypropylene (PP), rubber, EPDM, PVC, and stainless steel. Recommended for use on LSE substrates. Can resist short-term environmental conditions up to 180°C (356°F).



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA  
Customer Service: 800.IPG.8273 | 800.474.8273  
Tape Technical Service: 877.447.4832  
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 08/14

# INTERTAPE POLYMER GROUP® TECHNICAL DATA SHEET

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>Backing</b>	0.5 mil PET
<b>Adhesive</b>	Solvent Acrylic
<b>Adhesion to Steel</b> (oz/in) PSTC-101	63.5 (17.4 N/25mm)
<b>Elongation</b> (% at break) PSTC-133	118 MD 105 CD
<b>Service Temperature Range</b> Short Term	4°F to 356°F (-15°C to 180°C)
<b>Total Thickness w/o Liner</b> (mils) PSTC-133	8 (0.20mm)
<b>Liner Type</b> <b>Liner Thickness</b> (mils)	MOPP Film - Red 3.0 (0.08mm)
<b>Color</b>	Clear

